Transparent Data Encryption (TDE)

03/09/2017 • 10 minutes to read • Contributors

In this article

About TDE
Using Transparent Data Encryption
Commands and Functions
Catalog Views and Dynamic Management Views
Permissions
Considerations
Transparent Data Encryption and Buffer Pool Extension
Transparent Data Encryption and In-Memory OLTP
Related Tasks
Related Content
See Also

THIS TOPIC APPLIES TO: SQL Server Azure SQL Database Azure SQL Data Warehouse Parallel Data Warehouse

> For content related to previous versions of SQL Server, see Transparent Data Encryption (TDE).

Transparent Data Encryption (TDE) encrypts SQL Server, Azure SQL Database, and Azure SQL Data Warehouse data files, known as encrypting data at rest. You can take several precautions to help secure the database such as designing a secure system, encrypting confidential assets, and building a firewall around the database servers. However, in a scenario where the physical media (such as drives or backup tapes) are stolen, a malicious party can just restore or attach the database and browse the data. One solution is to encrypt the sensitive data in the database and protect the keys that are used to encrypt the data with a certificate. This prevents anyone without the keys from using the data, but this kind of protection must be planned in advance.

TDE performs real-time I/O encryption and decryption of the data and log files. The encryption uses a database encryption key (DEK), which is stored in the database boot record for availability during

FEEDBACK

recovery. The DEK is a symmetric key secured by using a certificate stored in the master database of the server or an asymmetric key protected by an EKM module. TDE protects data "at rest", meaning the data and log files. It provides the ability to comply with many laws, regulations, and guidelines established in various industries. This enables software developers to encrypt data by using AES and 3DES encryption algorithms without changing existing applications.

> **Important**
>
> TDE does not provide encryption across communication channels. For more information about how to encrypt data across communication channels, see **Enable Encrypted Connections to the Database Engine (SQL Server Configuration Manager)**.
>
> **Related topics:**
>
> - Transparent Data Encryption with Azure SQL Database
> - Get started with Transparent Data Encryption (TDE) on SQL Data Warehouse
> - Move a TDE Protected Database to Another SQL Server
> - Enable TDE on SQL Server Using EKM
> - Use SQL Server Connector with SQL Encryption Features
> - The SQL Server Security Blog on TDE with FAQ

About TDE

Encryption of the database file is performed at the page level. The pages in an encrypted database are encrypted before they are written to disk and decrypted when read into memory. TDE does not increase the size of the encrypted database.

Information applicable to SQL Database

When using TDE with SQL Database V12 the server-level certificate stored in the master database is automatically created for you by SQL Database. To move a TDE database on SQL Database you must decrypt the database, move the database, and then re-enable TDE on the destination SQL Database. For step-by-step instructions for TDE on SQL Database, see Transparent Data Encryption with Azure SQL Database.

Information applicable to SQL Server

After it is secured, the database can be restored by using the correct certificate. For more information about certificates, see SQL Server Certificates and Asymmetric Keys.

When enabling TDE, you should immediately back up the certificate and the private key associated with the certificate. If the certificate ever becomes unavailable or if you must restore or attach the database on another server, you must have backups of both the certificate and the private key or you will not be able

to open the database. The encrypting certificate should be retained even if TDE is no longer enabled on the database. Even though the database is not encrypted, parts of the transaction log may still remain protected, and the certificate may be needed for some operations until the full backup of the database is performed. A certificate that has exceeded its expiration date can still be used to encrypt and decrypt data with TDE.

Encryption Hierarchy

The following illustration shows the architecture of TDE encryption. Only the database level items (the database encryption key and ALTER DATABASE portions are user-configurable when using TDE on SQL Database.



Using Transparent Data Encryption

To use TDE, follow these steps.

Applies to: SQL Server.

- Create a master key
- Create or obtain a certificate protected by the master key

- Create a database encryption key and protect it by the certificate
- Set the database to use encryption

  The following example illustrates encrypting and decrypting the `AdventureWorks2012` database using a certificate installed on the server named `MyServerCert`.

SQL Copy

```sql
USE master;
GO
CREATE MASTER KEY ENCRYPTION BY PASSWORD = '<UseStrongPasswordHere>';
go
CREATE CERTIFICATE MyServerCert WITH SUBJECT = 'My DEK Certificate';
go
USE AdventureWorks2012;
GO
CREATE DATABASE ENCRYPTION KEY
WITH ALGORITHM = AES_128
ENCRYPTION BY SERVER CERTIFICATE MyServerCert;
GO
ALTER DATABASE AdventureWorks2012
SET ENCRYPTION ON;
GO
```

The encryption and decryption operations are scheduled on background threads by SQL Server. You can view the status of these operations using the catalog views and dynamic management views in the list that appears later in this topic.

> **Caution**
>
> Backup files of databases that have TDE enabled are also encrypted by using the database encryption key. As a result, when you restore these backups, the certificate protecting the database encryption key must be available. This means that in addition to backing up the database, you have to make sure that you maintain backups of the server certificates to prevent data loss. Data loss will result if the certificate is no longer available. For more information, see SQL Server Certificates and Asymmetric Keys.

Commands and Functions

The TDE certificates must be encrypted by the database master key to be accepted by the following statements. If they are encrypted by password only, the statements will reject them as encryptors.

> **Important**

> Altering the certificates to be password-protected after they are used by TDE will cause the database to become inaccessible after a restart.

The following table provides links and explanations of TDE commands and functions.

Command or function	Purpose
CREATE DATABASE ENCRYPTION KEY (Transact-SQL)	Creates a key that is used to encrypt a database.
ALTER DATABASE ENCRYPTION KEY (Transact-SQL)	Changes the key that is used to encrypt a database.
DROP DATABASE ENCRYPTION KEY (Transact-SQL)	Removes the key that was used to encrypt a database.
ALTER DATABASE SET Options (Transact-SQL)	Explains the **ALTER DATABASE** option that is used to enable TDE.

Catalog Views and Dynamic Management Views

The following table shows TDE catalog views and dynamic management views.

Catalog view or dynamic management view	Purpose
sys.databases (Transact-SQL)	Catalog view that displays database information.
sys.certificates (Transact-SQL)	Catalog view that shows the certificates in a database.
sys.dm_database_encryption_keys (Transact-SQL)	Dynamic management view that provides information about the encryption keys used in a database, and the state of encryption of a database.

Permissions

Each TDE feature and command has individual permission requirements, described in the tables shown earlier.

Viewing the metadata involved with TDE requires the VIEW DEFINITION permission on the certificate.

Considerations

While a re-encryption scan for a database encryption operation is in progress, maintenance operations to the database are disabled. You can use the single user mode setting for the database to perform the maintenance operation. For more information, see Set a Database to Single-user Mode.

You can find the state of the database encryption using the sys.dm_database_encryption_keys dynamic management view. For more information, see the "Catalog Views and Dynamic Management Views"section earlier in this topic).

In TDE, all files and filegroups in the database are encrypted. If any filegroups in a database are marked READ ONLY, the database encryption operation will fail.

If a database is being used in database mirroring or log shipping, both databases will be encrypted. The log transactions will be encrypted when sent between them.

> **Important**
>
> Full-text indexes will be encrypted when a database is set for encryption. Full-text indexes created prior to SQL Server 2008 will be imported into the database during upgrade to SQL Server 2008 or greater and they will be encrypted by TDE.

> **Tip**
>
> To monitor changes in the TDE status of a database, use SQL Server Audit or SQL Database Auditing. For SQL Server, TDE is tracked under the audit action group DATABASE_CHANGE_GROUP which can be found in SQL Server Audit Action Groups and Actions.

Restrictions

The following operations are not allowed during initial database encryption, key change, or database decryption:

- Dropping a file from a filegroup in the database
- Dropping the database
- Taking the database offline
- Detaching a database
- Transitioning a database or filegroup into a READ ONLY state

  The following operations are not allowed during the CREATE DATABASE ENCRYPTION KEY, ALTER DATABASE ENCRYPTION KEY, DROP DATABASE ENCRYPTION KEY, or ALTER DATABASE...SET ENCRYPTION statements.

- Dropping a file from a filegroup in the database.
- Dropping the database.

- Taking the database offline.
- Detaching a database.
- Transitioning a database or filegroup into a READ ONLY state.
- Using an ALTER DATABASE command.
- Starting a database or database file backup.
- Starting a database or database file restore.
- Creating a snapshot.

  The following operations or conditions will prevent the CREATE DATABASE ENCRYPTION KEY, ALTER DATABASE ENCRYPTION KEY, DROP DATABASE ENCRYPTION KEY, or ALTER DATABASE...SET ENCRYPTION statements.

- The database is read-only or has any read-only file groups.
- An ALTER DATABASE command is executing.
- Any data backup is running.
- The database is in an offline or restore condition.
- A snapshot is in progress.
- Database maintenance tasks.

  When creating database files, instant file initialization is not available when TDE is enabled.

  In order to encrypt the database encryption key with an asymmetric key, the asymmetric key must reside on an extensible key management provider.

Transparent Data Encryption and Transaction Logs

Enabling a database to use TDE has the effect of "zeroing out" the remaining part of the virtual transaction log to force the next virtual transaction log. This guarantees that no clear text is left in the transaction logs after the database is set for encryption. You can find the status of the log file encryption by viewing the `encryption_state` column in the `sys.dm_database_encryption_keys` view, as in this example:

Copy

```
USE AdventureWorks2012;
GO
/* The value 3 represents an encrypted state
   on the database and transaction logs. */
```